## 500°F / 260°C: FlameShield™ Silicone Rubber Self Fusing Compression & Stretch Electrical Insulating Tape Meets Lockheed Martin Space Systems 5-00857 & 5-00615 Specifications Self Binding Self-Fusing Tape - High Temperature, Heat & Flame Resistant



- Meets Lockheed-Martin 5-00857 & 5-00615 specifications.
- Self-bonds / self fuses / self amalgamating. No sticky residue or adhesive when removed. Starts fusing upon contact, fully bonded within hours. Excellent cold weather performance. Makes an excellent compression tape.
- Excellent for sealing ends of firesleeve: prevents sleeve from absorbing contamination and wicking liquids. Excellent for wrapping electrical & mechanical connections and splices. Makes clean and neat installations of cables, wires and hoses. Makes an instant separation bumper and provides vibration dampening.
- Meets Mil-I-46852 and AA59163 and other proprietary specifications.
- Supplied with Certification.

FlameShield™ High Temperat Meets Lockheed Mart	ure Silicone Rubber Seli in Space Systems 5-008		
Part Number	Tape Width Inches / mm	Tape Thickness inches / mm	Price Per Roll
	Specification 5-00857	•	
T-SR-5-00857-S-X-Y-ZZ	As per specification	As per specification	\$ by quote
	Specification 5-00615	5	
		1	

- For the X value, specify width
- For the Y value, specify thickness
- Standard roll length is 36 feet / 12 Yards / 10.9 Metres; other lengths available.
- For the ZZ value (color code): OR = Oxide-Red, BK = Black